

Powercutters

The right choice for the most demanding cutting requirements in construction and road building applications; fitted with powerful engines and state-of-the-art filtering devices in order to ensure trouble-free running even in dusty environments.

- ▶ Reversible cutting arm for improved access.
- ▶ Filtering system comprises 3-layer sponge prefilter, plus paper and nylon-mesh filters for unrivalled performance under all conditions.
- ▶ Electronic speed governor on coil.
- ▶ Cylinder with decompressor guarantees less stressful starting.
- ▶ Silicone-coated starting cord prevents swelling caused by water, fuel tank protected against sparks and accidental knocks.
- ▶ Machine supplied without disc.

TT 183 12"

Power	5 HP - 3.7 kW
Displacement	80.7 cm ³
Cutting disc diameter	300 mm
Max. cutting depth	120 mm
Weight without cutting disc	11.2 Kg



TT 183 14"

Power	5 HP - 3.7 kW
Displacement	80.7 cm ³
Cutting disc diameter	350 mm
Max. cutting depth	125 mm
Weight without cutting disc	11.4 Kg



TT 183 16"

Power	5 HP - 3.7 kW
Displacement	80.7 cm ³
Cutting disc diameter	400 mm
Max. cutting depth	150 mm
Weight without cutting disc	13.6 Kg



N.B.: photographs are purely indicative. The machine is supplied without disc.